Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	0	((runtime or run-time) with heap) and (heap with (prefetch$3 or pre-fetch$3 or preread$3 or pre-read$3 or readahead or (read$3 adj ahead)))	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:13
L2	23	((memory or address or storage) with (allocat$4 or allot$3) with (runtime or run-time)) and (prefetch$3 or pre-fetch$3 or preread$3 or pre-read$3 or readahead or (read$3 adj ahead))	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:13
L3	4	heap with (prefetch$3 or pre-fetch$3 or preread$3 or pre-read$3 or readahead or (read$3 adj ahead))	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:13
L4	1	(prefetch$3 or pre-fetch$3 or preread$3 or pre-read$3 or readahead or (read$3 adj ahead)) near5 heap	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:14
L5	4	(prefetch$3 or pre-fetch$3 or preread$3 or pre-read$3 or readahead or (read$3 adj ahead)) with heap	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:14
L6	2	((pointer with register) same (prefetch$3 or pre-fetch$3 or preread$3 or pre-read$3 or readahead or (read$3 adj ahead))) and (allocat$3 adj (range or pool))	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:14
L7	19	((address$3 with register) same (prefetch$3 or pre-fetch$3 or preread$3 or pre-read$3 or readahead or (read$3 adj ahead))) and (allocat$3 adj (range or pool))	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:14
L8	1	(pre-load$3 or preload$3) near10 heap	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:14
L9	3	(prefetch$3 or pre-fetch$3 or preread$3 or pre-read$3 or readahead or (read$3 adj ahead)) near10 heap	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:14
L10	0	(((prefetch$3 or pre-fetch$3 or preread$3 or pre-read$3 or readahead or (read$3 adj ahead)) or (pre-load$3 or preload$3)) near2 (range or subset or sub-set or set)) same ((dynamic or dynamically) near allocat$3)	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:15

L11	70	runtime and (((prefetch$3 or pre-fetch$3 or preread$3 or pre-read$3 or readahead or (read$3 adj ahead)) or (pre-load$3 or preload$3)) near2 (range or subset or sub-set or set))	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:16
L12	10	runtime same (((prefetch$3 or pre-fetch$3 or preread$3 or pre-read$3 or readahead or (read$3 adj ahead)) or (pre-load$3 or preload$3)) near2 (range or subset or sub-set or set))	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:16
L13	8	(allocat$4 near (pool or list or bucket)) with (prefetch$3 or pre-fetch$3 or preread$3 or pre-read$3 or readahead or (read$3 adj ahead))	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:16
L14	8	L13	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	NEAR	ON	2005/03/30 13:16
L15	4	heap with (prefetch$3 or pre-fetch$3 or preread$3 or pre-read$3 or readahead or (read$3 adj ahead))	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:17
L16	4	L15	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	NEAR	ON	2005/03/30 13:17
L17	9	heap same (prefetch$3 or pre-fetch$3 or preread$3 or pre-read$3 or readahead or (read$3 adj ahead))	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:17
L18	9	L17	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	NEAR	ON	2005/03/30 13:17
L19	5	(heap same (prefetch$3 or pre-fetch$3 or preread$3 or pre-read$3 or readahead or (read$3 adj ahead))) not (heap with (prefetch$3 or pre-fetch$3 or preread$3 or pre-read$3 or readahead or (read$3 adj ahead)))	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:17
L20	5	L19	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	NEAR	ON	2005/03/30 13:17

L21	1	(dynamic$4 near allocat$3) and ((prefetch$3 or pre-fetch$3 or preread$3 or pre-read$3 or readahead or (read$3 adj ahead)) near3 range)	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:17
L22	1	L21	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	NEAR	ON	2005/03/30 13:18
L23	8	range with ((((compare or compared or comparing or comparison) near3 (address or pointer or index)) with (prefetch$3 or pre-fetch$3 or preread$3 or pre-read$3 or readahead or (read$3 adj ahead)))	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:18
L24	8	L23	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	NEAR	ON	2005/03/30 13:18
L25	8	((prefetch$3 or pre-fetch$3 or preread$3 or pre-read$3 or readahead or (read$3 adj ahead)) with ((range or subset or sub-set) near2 (address or memory or storage))) same (((compare or compared or comparing or comparison) near3 (address or pointer or index)) with (prefetch$3 or pre-fetch$3 or preread$3 or pre-read$3 or readahead or (read$3 adj ahead)))	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:18
L26	8	L25	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	NEAR	ON	2005/03/30 13:18
L27	2	(dynamic$4 near allocat$3) with speculativ$3	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:18
L28	2	L27	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	NEAR	ON	2005/03/30 13:18
L29	17	(speculativ$3 near2 (read$3 or fetch$3 or load$3)) with heap	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:18

L30	17	L29	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	NEAR	ON	2005/03/30 13:18
L31	7	(speculativ$3 with heap) not ((speculativ$3 near2 (read$3 or fetch$3 or load$3)) with heap)	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:19
L32	7	L31	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	NEAR	ON	2005/03/30 13:18
L33	17	(speculativ$3 near2 (read$3 or fetch$3 or load$3)) same heap	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:18
L34	17	L33	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	NEAR	ON	2005/03/30 13:18
L35	21	allocat$3 with (speculativ$3 near2 (read$3 or fetch$3 or load$3))	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:18
L36	21	L35	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	NEAR	ON	2005/03/30 13:18
L37	0	(sub-set or subset) with (((compare or compared or comparing or comparison) near3 (address or pointer or index)) with (prefetch$3 or pre-fetch$3 or preread$3 or pre-read$3 or readahead or (read$3 adj ahead)))	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:18
L38	0	L37	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT ; IBM_TDB	NEAR	ON	2005/03/30 13:18

L39	43	((delimit$3 or de-limit$3) near5 address$3) with register	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:19
L40	43	L39	US-PGPUB; USPAT; EPO; JPO; DERWENT ; IBM_TDB	OR	ON	2005/03/30 13:19